



※ POWER CABLE : DURA & FLEX-F VU (0.5sqx2C) 5m

MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL NO	QLEX-SLM-250		
MATERIAL	HOUSING ( SIDE COVER ) - AL		
	HOUSING ( END COVER ) - AL		
	LENS ( GLOBE ) - PC		
COLOR OF LENS	CLEAR		
USE VOLT.	CURRENT	DC24V	MAX. 0.37A
PROTECTION GRADE	Ex d IIC T6 IP66/IP67		
CABLE ENTRY	M12xP1.5		

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	Ⓞ	v	-
0.5~3			±0.2		
3~6	±0.05	±0.1	±0.3	±0.5	
6~30	±0.1	±0.2	±0.5	±1	
30~120	±0.15	±0.3	±0.8	±1.5	
120~400	±0.2	±0.5	±1.2	±2.5	
400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°	
	10~50	±0°30'	±1°	±2°	
	50~120	±0°20'	±0°30'	±1°	
	120~400	±0°10'	±0°13'	±0°30'	

SURFACE FINISH

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	1	-
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
J.Y. KIM	Y.H. JOO		J.K. HAN	3	2019.03.20
TITLE			MODEL		
QLEX-SLM-250 LAYOUT			QLEX SERISE		
			DWG. NO.		
			QLEX LAYOUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		